

2 & 3 INCH THERMAL RECEIPT PRINTERS

**For Complete Hardware details see the next pages*



BT-58



RTP-82 UW



RTP-806



RTP-82 U



RTP-80

4 INCH BARCODE PRINTER



R-220



TTP-244

1D/2D BARCODE SCANNERS



LS-600



D-2060 N



D-5015



PD-2000+



PD-3000+



PD-4000+

POS MACHINE



RPS-6412

CASH DRAWER



RSK-410

WEIGHT SCALE



PHOENIX NPW



SI-810PR

CUSTOMER DISPLAY



PD-309 UE



THERMAL RECEIPT PRINTERS



₹ 2,500 (Incl. GST)

2 INCH BLUETOOTH+USB RECIEPT PRINTER

NIYAMA BT-58

Operating System	Windows, iOS, Android
Item Weight	0.21 Kilograms
Product Dimensions	27.9D x 35.6W x 12.7H Centimeters
Controller Type	iOS, Android
Included Components	1 User manual, 1 Paper Roll, 1 Charger Cable, 1 Printer
Print media	Unknown
Scanner Type	Portable
Compatible Devices	Smartphones
Sheet Size	58 Millimeters
Manufacturer	Niyama Enterprises
Country of Origin	China
Model number	BT-58
Number of Memory Sticks	4
Item Weight	205 g
Batteries	1 Lithium Ion batteries required. (included)
Item model number	BT-58
Power Source	Battery Powered
Resolution	203 x 203 DPI
Are batteries included?	Yes
Lithium battery energy content	2600 Milliamp Hours (mAh)
Lithium Battery Packaging	Batteries contained in equipment
Lithium battery weight	1 Grams
Number of lithium ion cells	1
Hardware Interface Type	Bluetooth, USB



NIYAMA BT-58

Print Commands ESC/POS Note-: This product required software development skill to integrate with android and iOS App, Programming Guide.

LIGHT WEIGHT: 205 Grams, Small Portable Size Easy to carry around. Pocket Friendly for bill printing in POS systems, super-markets, retail stores, restaurants, etc.

ZERO MAINTENANCE: . No ribbon, no ink cartridge. Printer Head has Life cycle upto 50 Kms

Auto Bluetooth Pairing, for hassle free operation.

Perfect product for Spot Printing, for billing, ticket and receipt

₹ 6,200 (Incl. GST)

RETSOL 82U

3 INCH THERMAL RECEIPT PRINTER- USB



Technical Specification

Model	RPT-82U
Printing method	Direct thermal
Paper width	58±0.5mm / 79.5±0.5mm
Print width	72mm / 76mm / 80mm / 64mm / 48mm / 52mm
Column capacity	576 dots / line (adjustable by command)
Printing Speed	200 mm/s
Line Spacing	3.75mm (Adjustable by commands)
Interface	USB
Auto cutter	Partial

Physical Characteristics

Weight	0.97 Kg
Dimensions	D 180 x W 140 x H 134.1mm

Reliability

Cutter life	1.5 million cuts
Printer head life	150Km

Software

Emulation	ESC/POS
Driver	Windows / JPOS / OPOS / Linux / Android / Mac
Utility	Windows & Linux test Utility
SDK	IOS / Android / Windows

Warranty

Warranty	One year factory warranty*	* Warranty - Against Manufacturing Defects on the Printer Specifications are subject to change without notice
----------	----------------------------	--



- New sleek shell design
- Wall mount capable
- Easy drop-in paper loading
- Intelligent cutter control system
- Order comes remind
- USB Interface

₹ 8,500 (Incl. GST)

3 INCH THERMAL RECEIPT PRINTER - USB + LAN



Technical Specification

Printer Model	Retsol RTP-80	
Printing	Printing Method	Direct thermal line printing
	Resolution	Default 203 dpi, 180 dpi can be emulated
	Printing Width	72mm(576dots)
	Printing Speed	Max. 230mm/s
	Printing Density	Adjustable from degree 1 to degree 4
	Printing Direction	Vertical and horizontal
Interfaces	Built-in USB, RS232, Ethernet	
Auto Cutter	Partial Cut	
Page Mode	YES	
Memory	RAM	2MB
	Flash	4MB
Barcode	1D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
	2D	QR code, PDF417
Detection	Sensor	Paper out, Cover Open
Power supply	Input	AC100V-240V 50-60HZ
	Output	DC 24V±5%, 2.0A,
Paper	Paper Loading	Front loading
	Paper Type	Standard Thermal Paper
	Paper Width	79.5±0.5mm
	Paper Thickness	0.056~0.13mm
	Paper Roll Diameter	83mm Max.
Reliability	TPH Life	150km
	Cutter Life	1,500,000 times
	Motor Life	360,000 hours
Packing Information	Accessories	Power Adaptor, RS232 Cable, CD, Quick Guide, Paper roll
Emulation	ESC/POS	
Driver	Windows(Win10/POSReady/Win8/Win7/Vista/XP/2000), Linux , OPOS	
Certifications	CE/CCC	
Eco Features	Paper Saving Mode, Energy Star qualified	
Warranty	One Year Factory Warranty*	



RETSOL RTP-80

- Triple Interfaces: USB, Ethernet & Serial
- Patent Design of Unique Vertical Double Auto Cutter
- Efficient & Stable Printing
- Easy Maintenance
- Supports Windows, Linux OS

₹ 8,500 (Incl. GST)

3 INCH THERMAL RECEIPT PRINTER USB + BLUETOOTH



Technical Specification

Model		RTP-82UB
Printing method	Direct thermal	
Paper width	58±0.5mm / 79.5±0.5mm	
Print width	72mm / 76mm / 80mm / 64mm / 48mm / 52mm	
Column capacity	576 dots / line (adjustable by command)	
Printing Speed	200 mm/s	
Line Spacing	3.75mm (Adjustable by commands)	
Interface	USB + Bluetooth	
Auto cutter	Partial	
Physical Characteristics		
Weight	0.97 Kg	
Dimensions	D 180 x W 140 x H 134.1mm	
Power		
Power adaptor	Input: AC 100-240V / 50~60Hz; Output: DC 24V / 2.5A	
Printer input	DC 24V / 2.5A	
Cash drawer	DC 24V / 1A	
Environmental Requirements		
Operational environment	Temperature (0 ~ 45°C) Humidity (10 ~ 80%)	
Storage environment	Temperature (-10 ~ 60°C) Humidity (10 ~ 90%)	
Reliability		
Cutter life	1.5 million cuts	
Printer head life	150Km	
Software		
Emulation	ESC/POS	
Driver	Windows / JPOS / OPOS / Linux / Android / Mac	
Utility	Windows & Linux test Utility	
SDK	IOS / Android / Windows	
Warranty		
Warranty	One year factory warranty*	

* Warranty - Against Manufacturing Defects on the Printer
Specifications are subject to change without notice

* Warranty - Against Manufacturing Defects on the Printer
Specifications are subject to change without notice



RETSOL RTP-82 UB

- New sleek shell design
- Wall mount capable
- Easy drop-in paper loading
- Intelligent cutter control system
- Order comes remind
- usb + Bluetooth Interfaces

₹ 9,500 (Incl. GST)



RETSOL 82UW

3 INCH THERMAL RECEIPT PRINTER - USB + WiFi

RTP-82UW

Technical Specifications

Printing method	Direct thermal
Paper width	58±0.5mm / 79.5±0.5mm
Print width	72mm/ 76mm/ 80mm/ 64mm/ 48mm/ 52mm
Column capacity	576 dots/line (adjustable by command)
Printing speed	200mm/s
Interface	USB + WiFi
Line spacing	3.75mm (Adjustable by commands)
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns/ Chinese, traditional Chinese - 21 columns or 24 columns
Character size	ANK, Font A:1.5×3.0mm (12×24 dots) Font B:1.1×2.1mm (9×16 dots) Chinese, traditional Chinese:3.0×3.0mm(24×24 dots)
Cutter life	1.5 Million cuts
Printer head life	150 Km
Emulation	ESC/POS
Driver	Windows/JPOS/OPOS/Linux/Android/Mac
Utility	Windows & Linux test Utility
SDK	IOS/Android/Windows
Warranty	One year factory warranty*

* Warranty - Against Manufacture
Specifications are subject to change



- New sleek shell design
- 200mm/s Printing Speed
- Wall mount capable
- Easy drop-in paper loading
- Intelligent cutter control system
- Order comes remind
- USB + WiFi Interfaces

₹ 9,500 (Incl. GST)

RETSOL TP-806



3 INCH THERMAL RECEIPT PRINTER - USB

Operating System	Windows XP, linux, Windows 8, Windows 7
Item Weight	1800 Grams
Product Dimensions	19.7D x 14.6W x 14.5H Centimeters
Printer Media Size Maximum	A8
Included Components	1 x Printer
Style	Thermal
Print media	Labels
Scanner Type	Portable
Sheet Size	32 x 15
Manufacturer	RETSOL
Model number	TP806
Form Factor	Printer
Number of Memory Sticks	1
Item Weight	1 kg 800 g
Item model number	TP806
Power Source	ac
Are batteries included?	No
Hardware Interface Type	USB, Ethernet



- » Patent design of unique vertical double auto cutter
- » Support page mode printing, with High Printing Speed 300mm/s, 1D & 2D Barcode Printing, 58 mm Paper Guide
- » Compatible with various width paper
- » Communication interfaces optional



BARCODE PRINTERS



₹ 11,000 (Incl. GST)

4 INCH BARCODE PRINTER



R220

Technical Specifications

Resolution	8 dots/mm (203 DPI)
Printing method	Thermal Transfer & Direct Thermal
Max. print speed	152 mm(6")/ second
Max. print width	108 mm (4.25")
Max. print length	25,400 mm (1,000")
Enclosure	PC and ABS plastic
Physical dimension	211 mm(W) x 164 mm(H) x 279 mm(D) 8.31"(W) x 6.46"(H) x 10.98"(D)
Weight	2.0 kg (4.41 lbs.)
Label roll capacity	127 mm (5")OD
Ribbon	300 m long, max. OD 67 mm, 1" core (ink coated outside) 110 m long, max. OD 40 mm, 0.5" core (ink coated outside)
Ribbon width	40 mm ~ 110 mm (1.6" ~ 4.3")
Processor	32-bit RISC CPU
Memory	16MB Flash, 64MB SDRAM
Interface	USB 2.0
Power	External universal switching power supply Input: AC 100-240V, 2.0A, 50-60Hz, Output: DC 24V, 2.0A, 48W
Operation switch	1 Power switch
Button, LED	1 operation button (pause/feed), LED (3 colors : green, orange & red)
Sensors	- Transmissive gap sensor - Black mark reflective sensor - Ribbon end sensor - Head open sensor
Internal fonts	8 alpha-numeric bitmap fonts Windows font can be downloaded by software
Barcode	- 1D barcode Code 128UCC, Code 128 subsets A, B, C, EAN128, Interleaved 2 of 5, Interleaved 2 of 5 with check digit, Code 39, Code 39 with check digit, Code 93, EAN13, EAN8, UPCA, UPCE, EAN and UPC 2 (5) digits add-on, Codabar, Postnet, MSI, MSI with check digit, PLESSEY, China post, ITF14, Code 11, TELEPEN, TELEPEN, PLANET, Code49, Deutsche Post Identcode, Deutsche Post Leitcode, LOGMARS - 2D barcode GS1 DataBar, GS1 DataMatrix, Maxicode, AZTEC, PDF417, QR Code, Micro PDF 417
Font and barcode rotation	0° x 90° x 180° x 270°
Printer language	TSPL-EZD (Compatible with EPL, ZPL, ZPL II, DPL)
Media type	Continuous, die-cut, black mark, fan-fold (outside wound)
Media width	19 ~ 118 mm (0.8" ~ 4.6")
Media thickness	0.06 ~ 0.19 mm (2.36 ~ 7.48 mil)
Media core diameter	25.4 mm (1.0")
Label length	5 ~ 25,400 mm (0.2" ~ 1000")
Environment condition	Operation: 0 ~ 40°C, humidity (non-condensing) 10 ~ 85% Storage: -20 ~ 60°C, humidity (non-condensing) 5 ~ 90%
Safety regulation	BIS, KC
Environmental concern	Comply with RoHS, REACH, WEEE
Accessories	Quick start guide, USB cable, Power cord, External universal switching power supply Label spindle x 1, fixing tab x 2, 1" ribbon spindle x 2, 0.5" ribbon spindle x 2
Warranty	One year for printer and six months or 25Km for printer head whichever is earlier



RETSOL R220

Features :

- Smooth printing experience
- Large supplies capacity - 300 meters (984') ribbon supply or 110 meters (361') ribbon supply on a 12.7 mm (0.5") core
- Print width up to 108 mm-supports multiple media types
- Position adjustable sensor - print precisely
- Automatic calibration - speed up printing test
- Media window design - easily check supplies stock status
- High-class thermal printing head - clear print quality and enhance durability
- User friendly design for easy installing media and ribbon
- USB 2.0 fast transmission speed
- Print quietly - low operation noise providing quality working environment
- Optimized heat radiation design - durable for large volume printing

₹ 13,500 (Incl. GST)



TSC TTP 244 BARCODE PRINTER

Barcode Printer

DESCRIPTION

Tsc Ttp 244 Pro.200 Mhz 32-Bit Risc Processor With 8 Mb Sdram
200 Mhz 32-Bit Risc Processor With 8 Mb Sdram,
4 Mb Flash Memory 203 Dpi
Internally Scalable True Type Fonts
5 Inches Per Second Print Speed
Usb 2.0 & Rs-232C Interfaces
300 Meter Ribbon Supply On A 1" Core (Coated Side Out)





BARCODE SCANNERS



₹ 3,000 (Incl. GST)

1D WIRED BARCODE SCANNER

RETSOL

RETSOL LS-600 Handheld Wired 1D Barcode Scanner with 32 Bit CPU, IP54 Protected Barcode reader.

PRODUCT DETAILS

Product Dimensions: 18 x 8 x 7 cm ; 499 g

Item model number: Ratsolbarcode

RETSOL LS-600 1D BARCODE SCANNER

Quick & Reliable Barcode Scanning Operations.

RETSOL presents LS 600, a handheld single line Laser Barcode Scanner that is designed to offer high performance data capture and catalog data as accurately as possible. It can easily scan common 1D barcodes directly from the paper even those having poor printing or scratches. It supports common 1D code such as EAN-8, EAN-13, UPC-A, UPC-E, Code 39, Code 128, EAN 128, Codabar, Industrial 2 of 5, Interleave 2 of 5, Matrix 2 of 5, MSI etc.



BARCODE SCANNER LS 600

₹ 3,800 (Incl. GST)

2D WIRED SCANNER

D-2060N

Technical Specification

Performance Parameters

Image (pixels)	640 pixels (H) X 480 pixels (V)
Light Source	Aiming: 617nm LED; illumination: 6500K LED
Field of View	40° (H) x 32° (V)
Scan Precision	4mil
Scan Speed	60 Frames/Second
Roll / Pitch / Yaw	360°, ±65°, ±60°
Print Contrast	25% Minimum Reflective Difference
Interfaces Supported	USB, RS-232

Physical Parameters

Dimensions	170mm x 95mm x 70mm
Weight	126g
Voltage	5V DC ± 10%
Current	300mA (operating)

Symbology Decode Capability

1D	UPC, EAN, Code128, Code39, Code93, Code11, Matrix 2 of 5, Interleaved 2 of 5 Codabar, MSI Plessey, GS1 Databar, China Postal, Korean Postal, Etc.
2D	PDF417, Micro PDF417, Data Matrix, Maxicode, QR Code, Micro QR Code, Aztec

User Environment

Operating Temperature	0°C to 50°C
Storage Temperature	-40°C to 70°C
Humidity	0% to 95% relative Humidity, Non-Condensing
Shock Specification	Designed to Withstand 1.5m(5') Drops
Ambient Light Immunity	100,000 Lux

Warranty

Warranty	2 Years - Factory Warranty *
----------	------------------------------

Performance may be impacted by barcode quality and environment.
* Warranty - Against manufacturing defects on the scanner.
Specifications are subject to change without notice.

RETSOL



RETSOL D-2060N

- Ergonomic & Sleek Design
- Comfortable to hold use
- Read all Mainstream 1D/2D Barcodes
- Low Power Consumption
- USB or RS-232 Interfaces

₹ 5,000 (Incl. GST)



2D WIRELESS SCANNER WITH BLUETOOTH



D-5015

Technical Specification

Performance Parameters

Resolution	640 pixels (H) X 480 pixels (V)
Light Source	617nm LED Aimer, White LED
Scan Mode	Manual, Continuous, Automatic Induction Scanning
Scanning Principle	Image CMOS
Print Contrast	≥10%
Scan angle	Yaw ±45°, Rotation 360°, Pitch ±45°
Precision	≥5 mil
Interface	USB-HID
Wireless transmission distance	up to 30 meters (Open distance)
Pairing mode	One Scanner Gun Pairs One Receiver, One Scanner paired with a Bluetooth mobile device
Storage mode	Offline mode - When the scanner exists the connection range the data is automatically stored Inventory mode - Scanner can enter inventory mode Storage capacity is 512000 characters

Symbology Decode Capability

1D	Code 128, EAN-13, EAN-8, UPC-E, UPC-A, ISBN, ISSN, Code 11, Interleaved 2 of 5, Code 39, Code 93, Code 32, Codabar, Matrix 2 of 5, Industrial 25, IATA25, MSI-Plessey, GS1 Databar, etc.
2D	QR Code, Micro QR, Data Matrix, PDF417, Micro PDF417, Aztec, Maxicode, Hanxin code, etc.

Physical Parameters

Environmental Parameters

Warranty

Warranty	1 Year - Factory Warranty for Scanner * 3 Months - Warranty for Battery
----------	--

Performance may be impacted by barcode quality and environmental conditions
* Warranty - Against manufacturing defects on the scanner
Specifications are subject to change without notice

RETSOL D-5015

- Can Interpret various 1D/2D codes & Support Chinese direct transmission of QR Code.
- USB Bluetooth Receiver supports plug & play, easy to set up & quickly match.
- Wireless Bluetooth transmission distance up to 30 meter (open area)
- 512,000 characters can be stored in offline/inventory storage mode.
- Can be paired directly with bluetooth enabled mobile phones, tablets & laptops.

₹ 5,700 (Incl. GST)

RETSOL PD-2000+

2D TABLE TOP BARCODE SCANNER

Brand	RETSOL
Manufacturer	RETSOL
Country of Origin	China
Model number	PD-2000
Number of Memory Sticks	1
Item Weight	470 g
Product Dimensions	16 x 11.4 x 10.2 cm; 470 Grams
Item model number	PD-2000
Item Height	10.2 Centimeters
Item Width	11.4 Centimeters
Connectivity Technology	USB Cable
Power Source	Corded Electric
Compatible Device	Laptop
Included Components	1 X Barcode Scanner Wireless



- » Captures 1D/2D Codes on Paper & LCD Displays
- » Large Field of View
- » Self Induction to Automatic Start Scan Engine
- » Super Large Reading Window
- » 3 Different Modes (Normal, Mobile Screen, Fast Moving)

₹ 7,500 (Incl. GST)

RETSOL PD-3000+
2D TABLE TOP BARCODE SCANNER

Brand	RETSOL
Manufacturer	RETSOL
Country of Origin	China
Model number	PD-3000
Number of Memory Sticks	1
Item Weight	525 g
Product Dimensions	20 x 14 x 12 cm; 525 Grams
Item model number	PD-3000
Item Height	12 Centimeters
Item Width	14 Centimeters
Connectivity Technology	USB Cable
Power Source	Corded Electric
Compatible Device	iPhone
Included Components	1 X Barcode Scanner Wireless



- » 1 Megapixel Imaging Sensor runs with a 1.2GHZ CPU
- » A Loud Scanning Alert Sound
- » Excellent Pass Through Scanning
- » Capture every Barcodes on paper & LED/LCD Screens
- » 3 Different Modes (Normal, Mobile Screen, Fast Moving)

₹ 9,200 (Incl. GST)

RETSOL PD-4000+
2D TABLE TOP BARCODE SCANNER



Brand	RETSOL
Manufacturer	RETSOL
Country of Origin	China
Model number	PD-4000
Number of Memory Sticks	1
Item Weight	525 g
Product Dimensions	20 x 14 x 12 cm; 525 Grams
Item model number	PD-4000
Item Height	12 Centimeters
Item Width	14 Centimeters
Connectivity Technology	USB Cable
Power Source	Corded Electric
Compatible Device	iPhone
Included Components	1 X Barcode Scanner Wireless



- » Object Self Induction
- » Build in USB Interface
- » Read all Mainstream 1D/2D Barcodes
- » Low Power Consumption, Strong Performance
- » Fast Mobile Phone Screen Barcode Reading



POS MACHINE



₹ 55,000 (Incl. GST)

RETSOL

RETSOL RPS-6412

POS TERMINAL

RPS-6412

Technical Specification

System Configuration

Processor	Intel Celeron J6412 CPU, Up to 2.6GHz, 1.5M Cache
System Memory	DDR4 3200MHz, SO-DIMM x 1, minimum 4GB, max support 32GB
Storage Device	SATA 2.5" HDD or M.2 SATA SSD minimum 128GB
Power Supply	DC12V/5A - 60W external power adapter. AC100 to 240V full range
O/S Support	Win 10 IoT, Win 10 PRO, Win11, Linux, Ubuntu

Physical Dimensions

Dimensions	Width: 360 / Height: 350 / Depth: 215
Weight(N.W in kg)	5 kg
Wall Mount	VESA 100 * 100 mm compliant
Product Certification	CE / FCC
Operation Temperature	0°C to 40°C
Storage Temperature	-20°C to 70°C

Display & Touch

LCD Display	15" Led LCD Panel , Brightness: 350 cd/m2 (default)
LCD Resolution	1024 x 768 (default)
Touch Function	10-point multi-touch, Projected Capacitive Touch , USB Interface

I/O Expansion

Standard USB Port	2 x USB 3.0 Port / 3 x USB 2.0 Port
LAN Port	1 Port RJ-45 LAN with activity and link LEDs 10/100/1000 Gb Ethernet
Serial Port	DB9 x 2 Port , COM1 & COM2
Audio	Buzzer Only (Speaker Option)
VGA Port	DB-15 x 1 Port
Extension Slot	Mini-PCI-e Slot x 2 (4G, WiFi)

Options

2nd Monitor	Back Mount 9.7" LED LCD Panel, 1024x768 Resolution, VGA/USB/HDMI Interface, PCAP Touch
MSR	2 or 3 Tracks, USB Interface
Customer Display	7mm VFD, 20 x 2 Line, RS-232 or USB Interface, Back mount or pole stand
WiFi	Mini PCI-E WiFi 802.11 b/g/n
SSD	M.2 SATA SSD Minimum 256GB or Higher



Highlights and Features

Drivers & Utility	VFD support OPOS & Java POS Driver
Trusted Platform Module for Windows	TPM2.0 Supported
Certification	CE / FCC / BIS Certified
Warranty	2 Years



WEIGHT SCALE



₹ 6,500 (Incl. GST)

PHOENIX NPW

PHOENIX NPW - 30KG WEIGHING SCALE (CAPACITY 30KG)

Technical Details

Brand	Phoenix
Colour	silver
Special Feature	Backlit Display
Display Type	LED
Weight Limit	30 Kilograms
Form Factor	Mini
Material	Acrylonitrile Butadiene Styrene
Readout Accuracy	30 Kilograms
Manufacturer	phoenix
Item part number	PH014
ASIN	B084X5ZWVY



For Pricing Contact Essae

WEIGHT SCALE WITH BARCODE PRINTING

Essae
Protecting YOUR Profits

Technical Specifications

Description	Barcode Label Printing Scale
Capacity/Accuracy	6kg / 1kg, 15kg / 2kg, 31kg / 5kg
Platter Size	280X348 mm
Label Width and Length (min~max)	25~54 mm, 257~110 mm
Label Thickness (max)	170 microns
PLU	5000
Printing speed	80 mm/sec
Label Roll Diameter (max)	Outer: 120 mm, Inner: 28 mm
Standard Interfaces	1 x RS-232 Serial, 1 x Ethernet LAN
Dimension (Lx W x D)	490 mm x 360 mm x 450 mm





CASH DRAWER



₹ 5,000 (Incl. GST)



CASH DRAWER RSK 410

PRODUCT DESCRIPTION



Physical Parameters Dimension:

410(W)x420(D)x100(H)mm Construction: Thick gauge cold rolled steel & SECC Finish: Textured hybrid powder coating Colour: Black Roller: Polyurethane for smooth operation.

Cash Tray [Insert] Construction:

Shatter - Resistance Plastic Currency Layout: 4,5,6,8 - Bill with Metal wire grips, 8 Adjustable coins slots.

Operation Drawer Lock:

3-Position Lock / 4 Functions: Locked Open / Closed, Manual Open, Electronically Driven Interface: RJ11

Life cycle: MTBF 1000000 times

Micro Switch: Cash Drawer Status Micro Switch

Warranty: 1 Year



CUSTOMER DISPLAY



For Pricing Contact Posiflex

LCD CUSTOMER DISPLAY

POSIFLEX

PD-309UE BASE-MOUNT LCD CUSTOMER DISPLAY

Display		Tilt Angle Adjustment	15°, 30° and 45°
Display Type	LCD	Horizontal Swivel Adjustment	-
Form Factor	Base-mount with pole (200 mm), 270° horizontal swivel		
Display Color	Blue or green	Supported Command Types	PST (Posiflex proprietary command) & ESC/POS
Dot Matrix/Resolution	5 x 7 dots	Physical Dimension	
Characters Available	12 international character sets	Dimension (W x D x H in mm)	
Character Number	20 characters x 2 lines	Weight (N. W. in g)	
Character Size	6.0 mm x 9.6 mm		
Multimedia Support	N/A		
Interface	USB (True USB/Virtual COM selectable)		